



POWERHOLD

General Purpose Contact Cement

500

DESCRIPTION

POWERHOLD™ 500 is a solvent-based rubber-resin general-purpose contact adhesive used for a wide variety of bonding applications.

USE FOR

Typical applications include bonding veneers, paneling, ceramic tile, stair treads, risers, cove base, transition and tack strips to other substrates.

BONDS TO

Wood, vinyl, rubber, leather, drywall, concrete, glass, ceramics and metal.

Test areas must be installed to determine suitability for intended use.

PREPARATION

READ ALL WARNINGS, FULL INSTRUCTIONS AND MSDS BEFORE OPENING CONTAINER.

Stir thoroughly with a wooden or metal paint paddle or stirring stick.

Pre-fit all parts before applying.

Bonding surfaces must be clean, dry and free of wax, oil or other release agents before applying.

INSTALLATION

Using a paintbrush, short nap roller or finishing trowel, apply an even coat of adhesive to both surfaces.

Allow adhesive to dry (approx. 5 to 10 min at 70°F/21°C).

Position pieces accurately as adhesive bonds instantly. Apply moderate pressure to ensure complete contact.

CLEANUP

Apply carefully as adhesive is difficult to remove when dry.

WARRANTY

1-Year Standard Limited Warranty applies. Failure to follow written directions will void the warranty. For complete warranty details, please contact our Customer Service Center at 1-800-232-4832.

NOTES

- Freeze / Thaw: Not affected by freezing.
- Shelf life is 1 year, if unopened.
- VOC Content: 596 g/L (less water and exempt compounds), calculated and reported, SCAQMD 1168.

Important Notice: This contact adhesive is for professional and industrial use only. The Consumer Product Safety Commission prohibits the sale of this adhesive to consumers for personal use in containers exceeding 8 fluid oz. (1/2 pint).

Made in the USA for:

FCDA / POWERHOLD

© 2013 FCDA / POWERHOLD. All rights reserved.
06-26-2013

FCDA / POWERHOLD

www.powerhold.net

FCDA

P.O. Box 7558

Fort Worth, TX 76111

(800) 232-4832 (Phone)